



Scientific and Technical Gases Ltd
 APV House, Speedwell Road,
 Parkhouse Industrial Estate,
 Newcastle under Lyme, Staffordshire,
 United Kingdom, ST5 7RG

TEL: +44 (0) 1782 566897
 FAX: +44 (0) 1782 564906
 EMAIL: info@stgas.eu
 WEBSITE: www.stgas.eu



**WORLDWIDE
 SUPPLIER OF
 QUALITY GAS
 PRODUCTS
 AND SERVICES**



STG/23/10.10



5ST/5AL - 5 LITRE STEEL/ALUMINIUM HIGH PRESSURE CYLINDERS

CONTENTS

Water Capacity - 5 Litres - 750L gas.

SERVICE PRESSURE

150bar.

DIMENSIONS

AL Height 505mm, Diameter 150mm.

ST Height 480mm, Diameter 140mm.

WEIGHTS

- **AL** - 8kg
- **ST** - 9kg

MATERIAL & VALVE TYPE

Aluminium - for reactive gases.

Steel - for non-reactive gases.

- British (BS).
- Europe (DIN).
- U.S.A. (CGA).

STANDARDS

NPL, UKAS or NIST standards.

Manufactured gravimetrically to ISO 6142. ISO 17025 also available.

EQUIPMENT

- Single Stage Brass - StG - B1
- Two Stage Brass - StG - B2
- Single Stage Stainless Steel - StG - S1
- Two Stage Stainless Steel - StG - S2

HP REGULATOR CODING

Scientific and Technical Gases Regulator Material B = Brass S = Stainless Steel

StG - B1 - 10 - BS4 - 14F

STAGES 1 = Single Stage 2 = Two Stage	Maximum Outlet Pressure e.g. 10bar	INLET FITTING* e.g. BS3 / BS4 / BS15 *CGA and DIN available	OUTLET CONNECTION 14F = 1/4" NPT Female 14M = 1/4" NPT Male 14SW = 1/4" Compression 14HB = 1/4" Hosebarb Options for 1/8" available
---	------------------------------------	--	--

WARRANTY

Non-reactive gases	up to 36 months
H ₂ S, SO ₂ and 4 gas mixtures	24 months
NO, NH ₃ , HCN, ETO	up to 24 months
Cl ₂ (min 5ppm)	12 months
HCl (min 5ppm)	up to 12 months
NO ₂	12 months

Cylinder heights are to the centre of outlet valve. Add 100mm or total absolute height with guard or cap.
 The above weights are cylinder and valve without contents.



MIXTURE TOLERANCES

Minor components are certified to the following analytical tolerance

- 2-20ppm = +/- 10%
- 21- 50ppm = +/- 5%
- 51-300ppm = +/- 2%

