

The Status Alarm II is a remote module lending itself to a wide variety of warning and alarm applications. The module provides a combined audible and 'text selectable' illuminated window indication. The audible sounder may be muted at any time or will automatically mute by default after a 5 minute period of continuous operation; the visual alarm window will remain illuminated until the alarm has cleared. An optional internal relay can also be provided to further extend the functionality of the Status Alarm II.

Supply	12~28vDC
Signal Input	12~28vDC
Power	2W
Indicators	Long Life LED's Green – safe condition Red – hazardous condition
Sounder	98 dB @ 30cm
Protection	IP65
Dimensions	120mm x 120mm x 60mm



Features	Remote reset terminals – N/O contacts (close to initiate a reset) Selectable window text – cut out text and position to rear of window Permanent sounder mute – remove JP2 to initiate Latched alarm until reset – remove JP1 to initiate Relay - rated 230V AC / 3A Cable entry – Top/bottom/sides/rear
-----------------	---

Operational Status:-

Normal State	Green indicator on Red indicator off Sounder off
Alarm State	Green indicator off Red indicator on Sounder on
Auto Reset Alarm Mode	Green indicator off Red indicator flashing Sounder on with auto-mute after 5 minutes
Mute/Reset Operation) (alarm present)	Green indicator off Red indicator constant Sounder off
Mute/Reset Operation (alarm signal cleared)	Green indicator on Red indicator off Sounder off
Latched Alarm	Green Indicator off Red indicator on until operation of Mute/Reset.

