



# DoseRAE Pro

Rugged Electronic Dosimeter for Personal Radiation Dosage Monitoring



DoseRAE Pro is a rugged, compact, direct-reading and alarming electronic personal radiation detector and dosimeter. It uses a diode and a scintillation crystal to detect X- ray and gamma radiation, and provides real-time monitoring of personal dose and dose-rate allowing immediate action to reduce personal radiation exposure. DoseRAE Pro includes a Stay-time countdown timer with warning alarm to allow the user to set a specific time limit when working in a radiation area, limiting the users personal radiation exposure.

- Dosimeter and PRD functionality in a rugged, compact package
- Wide dose rate range and energy range maximizes personal protection
- Fast response time to immediately detect radiation threats
- Ease of use minimizes personnel training & support costs and reduces total cost of ownership

## KEY FEATURES

- Rugged electronic dosimeter with high sensitivity CsI Scintillator sensor
- Multiple units with reader and software can be used as a dosimetry system
- Continuous LCD digital dose rate readout in Sv/h or R/h
- Continuously accumulated total dose readout in Sv or R
- Prominent visible, audible, and vibration alarms
- User configurable Stay-Time countdown timer and alarms to prevent excessive radiation exposure
- Fast near field communication wireless data transfer
- Long calibration life
- Simple two button operation and programming

## APPLICATIONS

- Nuclear power plants
- Environmental survey and clean-up
- Fire Departments
- Hazardous Material Response Teams
- Police
- EMS
- Military
- Industrial safety
- Waste management
- Hospitals and Medical Clinics



Fast dosimeter programming and data download via robust wireless Near Field Communications to the optional Dosimeter Reader



# DoseRAE Pro



Rugged Electronic Dosimeter for Personal Radiation Dosage Monitoring

## SPECIFICATIONS

Sensors	
Gamma Sensors	CsI (TI) + photodiode (low environment radiation) Energy-compensated PIN diode (level of radiation protection)
Dose Rate Range	0.01 $\mu$ Sv/h to 9.99 Sv/h (1 $\mu$ R/h to 999 R/h)
Accuracy of Dose Rate	$\pm$ 20% (from 10 $\mu$ Sv/h to 9.99 Sv/h or from 1mR/h to 999 R/h) $\pm$ 30% (from 0.01 $\mu$ Sv/h to 10 $\mu$ Sv/h or 1 $\mu$ R/h to 1 mR/h)
Dose Range	0.01 $\mu$ Sv to 9.99Sv (1 $\mu$ R to 999R)
Dose Accuracy	$\pm$ 15%
Energy Range	50 keV to 6 MeV for X- and gamma radiations
Alarms	
Alarm Alerts	<ul style="list-style-type: none"><li>• Loud audible buzzer (85+dB @ 30 cm/12")</li><li>• Highly visible LED lights</li><li>• Built-in vibration alarm</li><li>• Each alarm individually enabled/disabled</li></ul>
Alarm Settings	<ul style="list-style-type: none"><li>• Dose: continuously adjustable: 1 <math>\mu</math>Sv to 9.99 Sv (100 <math>\mu</math>R to 999 R)</li><li>• Dose Rate: continuously adjustable: 1 <math>\mu</math>Sv/h to 9.99 Sv/h (100 <math>\mu</math>R/h to 999 R/h)</li><li>• Stay Time: 1 to 999 min.</li><li>• "Chirp" alarm: 1 beep per accumulated dose increment (1 <math>\mu</math>Sv to 9.99Sv or 100<math>\mu</math>R to 999R)</li><li>• All alarm settings are passcode protected with 3 digit code</li><li>• Low battery alert when 48 hours of life remain</li></ul>
Datalogging and Communications	
Data Storage	3000 points
Datalog Interval	User programmable, from 30 to 3,600 seconds
Communication	Near-field Communications to optional PRR-1 Dosimeter Reader for datalog download, dosimeter programming, factory configuration, calibration and firmware upgrade
Power	
Battery	1 AA alkaline battery, easily accessible with a coin
Operating Hours	750 hours of continuous use
Operating Environment	
Temperature	Operating: -20° to +50°C (-4° to +122°F) Storage: -30° to +70°C (-22° to +158°F)
Humidity	5 to 95%, non-condensing
Shock Resistance	Drop tested from 1.5m (4.9 ft.) onto hardwood surface
IP Rating	IP-54
Physical Characteristics	
Display	LCD display with pushbutton backlight Three-digit floating-point readout
Direct Readout	Dose and dose rate, autoranging in units of $\mu$ Sv, mSv, or Sv ( $\mu$ R, mR, or R)
User Interface	2 buttons
Size	52 x 89 x 924 mm (2" x 3.5" x 0.9") without clip
Weight	130g (4.6 oz.) with battery and clip
Attachments	Rugged metal alligator clip and belt clip

Specifications are subject to change

## DOSERAE PRO KIT INCLUDES:

- DoseRAE Pro electronic personal dosimeter with belt clip
- Alligator clip
- 1 AA battery
- User manual on CD
- Quick-start user guide
- Calibration and test certificate
- Warranty/registration card

## Optional Equipment:

- PRR-1 DoseRAE Pro Dosimeter Reader and software

## ORDERING INFORMATION ((MODEL PRM-1300))

Product	Part Number
DoseRAE Pro Dosimeter Kit—US version (display unit: R)	R04-0002-000
DoseRAE Pro Dosimeter Kit—EU version (display unit: Sv)	R04-0001-000

## CORPORATE HEADQUARTERS

### RAE Systems by Honeywell

3775 North First Street  
San Jose, CA 95134 USA  
raesales@raesystems.com

## WORLDWIDE SALES OFFICES

**USA/Canada** 1.877.723.2878  
**Europe** +45.86.52.51.55  
**Middle East** +00971.4.440.5949  
**China** +86.10.5885.8788-3000  
**Asia Pacific** +852.2669.0828