ToxiRAE3 for EMS First Responders

Personal Gas Monitor for CO



Lowest cost of ownership on the market

Rugged stainless-steel housing for harsh environments

Highly resistant to EMI/RFI

Fastest instrument response time on the market, for better protection and worker safety

Fastest bump station on the market, with highest productivity, putting workers back to work quickly

The ToxiRAE 3 is a full-featured single-gas monitor that offers unequaled cost of ownership value. The ToxiRAE 3 is compatible with the AutoRAE Lite bump and calibration station. The detector features a 2-year warranty.

Key Features

- Large, easy-to-read display for gas concentration or days remaining (end-user adjustable)
- Event logging of up to 10 events
- Full activity records when used with AutoRAE Lite calibration station
- Simple to operate
- Water- and dust-resistant (IP-67)
- Loud, 95dB audible alarm, bright red flashing visible LEDs, and internal vibration alarm
- Extended operating temperature of -4° to 140° F (-20° to +60° C)
- User-configurable bump/ calibration reminders

"The AutoRAE Lite bump and calibration station makes the system easy to maintain."

-JEMS September 2009

Bump testing ToxiRAE 3 with AutoRAE Lite **Bump Test and** Calibration Station



"The ToxiRAE3 CO Monitor from RAE Systems is an easy to use, *single-gas monitor that can be quickly* attached to a first-in bag to monitor the atmosphere."

-JEMS September 2009









Specifications

Sensor Specifications*

Gas	Range (ppm)	Resolution (ppm)	
со	0 to 500	1	

Detector Specifications*

Size	3.4" x 2.2" x 0.8" (8.6 cm x 5.5 cm x 2.0 cm)		
Weight	3.5 oz (99.4 g)		
Battery	User-replaceable 2/3 AA high-capacity lithium		
Alarms	 95dB typical (at 30 cm) buzzer and flashing red LED to indicate exceeded preset limits High: Displays "High" and emits 3 beeps and flashes per second Low: Displays "Low" and emits 2 beeps and flashes per second STEL: Displays "STEL" and emits 1 beep and flash per second TWA: Displays "TWA" and emits 1 beep and flash per second Vibration alarm 6-LED visible alarm 		
Data logging	10 events		
Response time	T90 < 12 seconds		
IP Rating	IP-67		
EMI/RFI	Highly resistant to EMI/RFI. Compliant with EMC directive 89/336/EEC		
Certification	US and Canada: C1D1, Groups A, B, C, D, T4 Europe: ATEX II 1G EEx ia IIC T4 IECEX: Ex ia IIC T4		
Operating Temperature	Continuous: -4° to 140° F (-20° to +60° C) Intermittent: -22° to 140° F (-30° to +60° C)		
Humidity	0 to 95% relative humidity (non-condensing)		
Warranty	2 years, including sensor and battery if used within specs		
Calibration	Two-point calibration for zero and span		

*Specifications are subject to change

ToxiRAE 3 Ordering Options

Pack of 1

ToxiRAE 3 with specified sensor:

- 2/3 AA lithium battery
- One mini-CD with instruction manual and training materials
- Alligator clip
- Calibration adapter

Pack of 10

- 10 ToxiRAE 3 monitors with specified sensor
- 2 mini-CDs with instruction manual and training materials
- 2 calibration adapters
- 10 alligator clips

Pack of 100

10 packs of 10

Ordering Information

ToxiRAE 3 for CO Monitor

Monitors	1 to 9 Units	10 to 99 Units	Pack of 100
Part #s	G01-0101-000	G01-0101-010	G01-0101-100

Calibration Accessories

Accessories	AutoRAE Lite Bump Test and Calibration Station	103L Cylinder of CO for use in AutoRAE Lite	CO Cal ibration Kit (if not using AutoRAE Lite)
Part #s	T01-0100-000	600-1000-000	007-3112-000



www.raesystems.com

RAE Systems Inc. 3775 North First Street San Jose, CA 95134 USA raesales@raesystems.com

USA/Canada 1-877-723-2878 Europe/Russia +45 8652 5155 Middle East / Australia +971 4 3639 427

China +86 10 58858788 Asia +852 2669 0828

Toll-Free: 877-723-2878



DS-1060-01